



SVC/ SVC-S SERIES

3000 - 15000 VA

Servo Type

1Ph - 1Ph

SVC/SVC-S SERIES

3000 - 15000 VA



Power (VA)	S3000	S5000	3000	5000	8000	10000	15000	توان
Input	145~250 VAC /50~60Hz		155~250 VAC /50~60Hz				بازه ولتاژ ورودی	
Output	220 VAC +/- 3 % / 50~60Hz		220 VAC +/- 3 % / 50~60Hz (option:110VAC-3000~5000)				ولتاژ خروجی	
Over Voltage Cutting	280 +/- 5V		280 +/- 5V				ولتاژ قطع بالا (ورودی)	
Power Factor	0.8		0.8				ضریب توان	
Temperature	(-5) to 45°		(-5) to 40°				دمای کارکرد	
Over Voltage Protection	245 +/- 5V		245 +/- 5V				ولتاژ قطع بالا (خروجی)	
Efficiency	> 95 %		> 95 %				بازدهی	
Max Output Current (A)	11	18	11	18	29	36	54	ماکسیمم جریان خروجی
Package Size (mm)	430 x 380 x 260	550 x 500 x 260	420 x 325 x 340	480 x 355 x 215	550x350x310		495 x 420 x 800	ابعاد (میلی متر)
Weight (kg)	17.5	23	17.5	23	47	50	60	وزن (کیلوگرم)

